# AERO American Made RF Adapters



Part Number

### A29M-29M

Description

## 2.92mm Male to 2.92mm Male

#### **Component Materials**

**Component Plating** 

Body

Bushing Sleeve(s) Contact

| Body      | 303 Stainless Steel |
|-----------|---------------------|
| Bushing   | 303 Stainless Steel |
| Sleeve(s) | 303 Stainless Steel |
| Contact   | Brass               |
| Snap Ring | Beryllium Copper    |
| Insulator | Ultem 1000          |
| Gasket    | Silicone (Red)      |

#### **Electrical Specifications**

| Impedance                               | 50 Ohm             |
|---|--------------------|
| Frequency Range                         | DC to 40 GHz       |
| VSWR                                    | 1.15 Max to 40 GHz |
| Voltage Rating (AC)                     | 500 Vrms           |
| Insulation Resistance                   | N/A                |
| Dielectric Withstanding<br>Voltage (AC) | 1,500 Vrms         |

#### **Mechanical Specifications**

| Passivate        | Polarity                   | 2.92mm Male to Standard 2.92mm |
|------------------|----------------------------|--------------------------------|
| Passivate        |                            | Male                           |
| Passivate        | Interface<br>Specification | IEEE Std 287                   |
| Gold over Nickel | Mating Cycles              | 500                            |

#### **Environmental Specifications**

Operating Temperature Range

-65° C to +165° C

#### **Compliance Specifications**

RoHS and REACH Compliant DFARS Compliant