



Part Number

A24F-29M

Description

2.4mm Female to 2.92mm Male

### **Component Materials**

**Body** 303 Stainless Steel

Sleeve 303 Stainless Steel

**Bushings** Brass

Coupling Bushing 303 Stainless Steel

2.4mm Male Contact

Beryllium Copper

2.92mm Female

Contact

Beryllium Copper

Adaptor Contact Brass

Gasket Silicone (Red)

Snap Ring: Beryllium Copper

#### **Component Plating**

**Body** Passivate

**Bushing** Passivate

**Contact** Gold over Nickel

Sleeve Passivate

**Adaptor** 

Bushing Passivate

### **Environmental Specifications**

**Operating** 

Temperature -65° C to +165° C

Range

## **Electrical Specifications**

Impedance 50 Ohm

Frequency Range DC to 40 GHz

VSWR 1.3 Max to 40 GHz

Voltage Rating (AC) 250 Vrms

Insulation Resistance N/A

Dielectric Withstanding 500 Vrms

Voltage (AC)

# **Mechanical Specifications**

Polarity 2.4mm Female to Standard 2.92mm

Male

Interface IEEE Std 287

Mating Cycles 500

#### **Compliance Specifications**

**RoHS and REACH Compliant** 

**DFARS Compliant**