

2018

RF Adapter Catalog



Global Test Equipment

[www.4gte.com](http://www.4gte.com)

**Contents** (Click below to jump to the selected page)

2.4mm Adapters .....	3
2.92mm Adapters .....	4
3.5mm Adapters .....	5
SMA Adapters .....	6
Type N Adapters.....	7
2.4mm to 3.5mm Adapters.....	8
3.5mm to Type N Adapters.....	9
Type N to SMA Adapters.....	10
BNC to SMA Adapters .....	11




---

**Can't find what you need?**





**Included in this document are the most common adapters available at Global Test Equipment. Please contact us for information about additional configurations available.**



## 2.4mm Adapters in Stock




			
	<b>PA2222A</b>	<b>PA2222B</b>	<b>PA2222C</b>
Application	Precision Adapter	Precision Adapter	Precision Adapter
Compliance RoHS	Yes	Yes	Yes
Frequency Range	DC-50 GHz	DC-50 GHz	DC-50 GHz
VSWR	1.15 Max	1.15 Max	1.15 Max
Temperature	-55°C~+165°C	-55°C~+125°C	-55°C~+125°C
Body Material	Stainless Steel	Stainless Steel	Stainless Steel
Body Finish	Passivated	Passivated	Passivated
Contact Material	Beryllium Copper Alloy	Beryllium Copper Alloy	Beryllium Copper Alloy
Contact Finish	Gold	Gold	Gold
Insulator	PEI	PEI	PEI
Product Type	In Series	In Series	In Series
Convert From	2.4mm Plug	2.4mm Plug	2.4mm Jack
Convert To	2.4mm Plug	2.4mm Jack	2.4mm Jack
Impedance	50-Ohm	50-Ohm	50-Ohm
Price (Qty 1-9)	<b>\$ 89.00</b>	<b>\$ 89.00</b>	<b>\$ 89.00</b>

- To order on-line visit: <https://4gte.com/catalogsearch/result/?q=pa2222>
- To order by phone call us at 866-409-0400
- To order via with Net 30 terms, e-mail us at [sales@4gte.com](mailto:sales@4gte.com)





 <p><b>VELOCITY</b> MICROWAVE www.VelocitybyGTE.com</p>		<p><b>SUSTAINABLE SOLUTIONS</b></p> <ul style="list-style-type: none"> <li>• Save Money</li> <li>• Save Time</li> <li>• Save the Environment</li> </ul>
<p><b>Repairable Test Cables</b></p> 	<p><b>Connector Gage Sets</b></p> 	<p><b>Connector Torque Wrenches</b></p> 



## 2.92mm Adapters in Stock




			
	<b>PA2929A</b>	<b>PA2929B</b>	<b>PA2929C</b>
Application	Precision Adapter	Precision Adapter	Precision Adapter
Compliance RoHS	Yes	Yes	Yes
Frequency Range	DC-40 GHz	DC-40 GHz	DC-40 GHz
VSWR	1.15 Max	1.15 Max	1.20 Max
Temperature	-55°C~+125°C	-55°C~+125°C	-55°C~+125°C
Body Material	Stainless Steel	Stainless Steel	Stainless Steel
Body Finish	Passivated	Passivated	Passivated
Contact Material	Beryllium Copper Alloy	Beryllium Copper Alloy	Beryllium Copper Alloy
Contact Finish	Gold	Gold	Gold
Insulator	PEI	PEI	PEI
Product Type	In Series	In Series	In Series
Convert From	2.92 mm Plug	2.92 mm Plug	2.92 mm Jack
Convert To	2.92 mm Plug	2.92 mm Jack	2.92 mm Jack
Impedance	50-Ohm	50-Ohm	50-Ohm
Price (Qty 1-9)	<b>\$ 89.00</b>	<b>\$ 89.00</b>	<b>\$ 89.00</b>

- To order on-line visit: <https://4gte.com/catalogsearch/result/?q=pa2929>
- To order by phone call us at 866-409-0400
- To order via with Net 30 terms, e-mail us at [sales@4gte.com](mailto:sales@4gte.com)





		<b>SUSTAINABLE SOLUTIONS</b> <ul style="list-style-type: none"> <li>• Save Money</li> <li>• Save Time</li> <li>• Save the Environment</li> </ul>
<b>Repairable Test Cables</b> 	<b>Connector Gage Sets</b> 	<b>Connector Torque Wrenches</b> 



## 3.5mm Adapters in Stock

			
	<b>PA2525A</b>	<b>PA2525B</b>	<b>PA2525C</b>
Application	Precision Adapter	Precision Adapter	Precision Adapter
Compliance RoHS	Yes	Yes	Yes
Frequency Range	DC-33 GHz	DC-33 GHz	DC-33 GHz
VSWR	1.15 Max	1.15 Max	1.15 Max
Temperature	-55°C~+125°C	-55°C~+125°C	-55°C~+125°C
Body Material	Stainless Steel	Stainless Steel	Stainless Steel
Body Finish	Passivated	Passivated	Passivated
Contact Material	Beryllium Copper Alloy	Beryllium Copper Alloy	Beryllium Copper Alloy
Contact Finish	Gold	Gold	Gold
Insulator	PEI	PEI	PEI
Product Type	In Series	In Series	In Series
Convert From	3.5 mm Plug	3.5 mm Plug	3.5 mm Jack
Convert To	3.5 mm Plug	3.5 mm Jack	3.5 mm Jack
Impedance	50-Ohm	50-Ohm	50-Ohm
Price (Qty 1-9)	<b>\$ 109.00</b>	<b>\$ 109.00</b>	<b>\$ 109.00</b>

- To order on-line visit: <https://4gte.com/catalogsearch/result/?q=pa2525>
- To order by phone call us at 866-409-0400
- To order via with Net 30 terms, e-mail us at [sales@4gte.com](mailto:sales@4gte.com)

 <p><b>VELOCITY</b> MICROWAVE www.VelocitybyGTE.com</p>		<p><b>SUSTAINABLE SOLUTIONS</b></p> <ul style="list-style-type: none"> <li>• Save Money</li> <li>• Save Time</li> <li>• Save the Environment</li> </ul>
<p><b>Repairable Test Cables</b></p> 	<p><b>Connector Gage Sets</b></p> 	<p><b>Connector Torque Wrenches</b></p> 









## SMA Adapters in Stock




			
	<b>PA2121A</b>	<b>PA2121B</b>	<b>PA2121C</b>
Application	Precision Adapter	Precision Adapter	Precision Adapter
Compliance RoHS	Yes	Yes	Yes
Frequency Range	DC-26.5 GHz	DC-26.5 GHz	DC-26.5 GHz
VSWR	1.15 Max	1.15 Max	1.15 Max
Temperature	-55°C~+125°C	-55°C~+125°C	-55°C~+125°C
Body Material	Stainless Steel	Stainless Steel	Stainless Steel
Body Finish	Passivated	Passivated	Passivated
Contact Material	Beryllium Copper Alloy	Beryllium Copper Alloy	Beryllium Copper Alloy
Contact Finish	Gold	Gold	Gold
Insulator	PTFE & PEI	PTFE & PEI	PTFE & PEI
Product Type	In Series	In Series	In Series
Convert From	SMA Plug	SMA Plug	SMA Jack
Convert To	SMA Plug	SMA Jack	SMA Jack
Impedance	50-Ohm	50-Ohm	50-Ohm
Price (Qty 1-9)	<b>\$ 29.00</b>	<b>\$ 29.00</b>	<b>\$ 29.00</b>

- To order on-line visit: <https://4gte.com/catalogsearch/result/?q=pa2121>
- To order by phone call us at 866-409-0400
- To order via with Net 30 terms, e-mail us at [sales@4gte.com](mailto:sales@4gte.com)





 <p><b>VELOCITY</b> MICROWAVE www.VelocitybyGTE.com</p>		<p><b>SUSTAINABLE SOLUTIONS</b></p> <ul style="list-style-type: none"> <li>• Save Money</li> <li>• Save Time</li> <li>• Save the Environment</li> </ul>
<p><b>Repairable Test Cables</b></p> 	<p><b>Connector Gage Sets</b></p> 	<p><b>Connector Torque Wrenches</b></p> 



## Type N Adapters in Stock





			
	<b>PA5151A</b>	<b>PA5151B</b>	<b>PA5151C</b>
Application	Precision Adapter	Precision Adapter	Precision Adapter
Compliance RoHS	Yes	Yes	Yes
Frequency Range	DC-18 GHz	DC-18 GHz	DC-18 GHz
VSWR	1.15 Max	1.15 Max	1.15 Max
Temperature	-55°C~+125°C	-55°C~+125°C	-55°C~+125°C
Body Material	Stainless Steel	Stainless Steel	Stainless Steel
Body Finish	Passivated	Passivated	Passivated
Contact Material	Beryllium Copper Alloy	Beryllium Copper Alloy	Beryllium Copper Alloy
Contact Finish	Gold	Gold	Gold
Insulator	PEI	PEI	PEI
Product Type	In Series	In Series	In Series
Convert From	Type N Plug	Type N Plug	Type N Jack
Convert To	Type N Plug	Type N Jack	Type N Jack
Impedance	50-Ohm	50-Ohm	50-Ohm
Price (Qty 1-9)	<b>\$ 59.95</b>	<b>\$ 59.95</b>	<b>\$ 39.95</b>

- To order on-line visit: <https://4gte.com/catalogsearch/result/?q=pa5151>
- To order by phone call us at 866-409-0400
- To order via with Net 30 terms, e-mail us at [sales@4gte.com](mailto:sales@4gte.com)





		<b>SUSTAINABLE SOLUTIONS</b> <ul style="list-style-type: none"> <li>• Save Money</li> <li>• Save Time</li> <li>• Save the Environment</li> </ul>
<b>Repairable Test Cables</b> 	<b>Connector Gage Sets</b> 	<b>Connector Torque Wrenches</b> 



## 2.4mm to 3.5mm Adapters in Stock

				
	<b>PA2225A</b>	<b>PA2225B</b>	<b>PA2225C</b>	<b>PA2225D</b>
Application	Precision Adapter	Precision Adapter	Precision Adapter	Precision Adapter
Compliance RoHS	Yes	Yes	Yes	Yes
Frequency Range	DC-33 GHz	DC-33 GHz	DC-33 GHz	DC-33 GHz
VSWR	1.15 Max	1.15 Max	1.15 Max	1.15 Max
Temperature	-55°C~+125°C	-55°C~+125°C	-55°C~+125°C	-55°C~+125°C
Body Material	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel
Body Finish	Passivated	Passivated	Passivated	Passivated
Contact Material	Beryllium Copper Alloy	Beryllium Copper Alloy	Beryllium Copper Alloy	Beryllium Copper Alloy
Contact Finish	Gold	Gold	Gold	Gold
Insulator	PEI	PEI	PEI	PEI
Product Type	Between Series	Between Series	Between Series	Between Series
Convert From	2.4mm Plug	2.4mm Plug	2.4mm Jack	2.4mm Jack
Convert To	3.5mm Plug	3.5mm Jack	3.5mm Jack	3.5mm Plug
Impedance	50-Ohm	50-Ohm	50-Ohm	50-Ohm
Price (Qty 1-9)	<b>\$ 149.95</b>	<b>\$ 149.95</b>	<b>\$ 129.95</b>	<b>\$ 149.95</b>



- To order on-line visit: <https://4gte.com/catalogsearch/result/?q=PA2225>
- To order by phone call us at 866-409-0400
- To order via with Net 30 terms, e-mail us at [sales@4gte.com](mailto:sales@4gte.com)

		<b>SUSTAINABLE SOLUTIONS</b> <ul style="list-style-type: none"> <li>• Save Money</li> <li>• Save Time</li> <li>• Save the Environment</li> </ul>	
<b>Repairable Test Cables</b> 	<b>Connector Gage Sets</b> 	<b>Connector Torque Wrenches</b> 	









## 3.5mm to Type N Adapters in Stock



		
	<b>PA5125A</b>	<b>PA5125B</b>
Application	Precision Adapter	Precision Adapter
Compliance RoHS	Yes	Yes
Frequency Range	DC-18 GHz	DC-18 GHz
VSWR	1.15 Max	1.15 Max
Temperature	-55°C~+125°C	-55°C~+125°C
Body Material	Stainless Steel	Stainless Steel
Body Finish	Passivated	Passivated
Contact Material	Beryllium Copper Alloy	Beryllium Copper Alloy
Contact Finish	Gold	Gold
Insulator	PEI	PEI
Product Type	Between Series	Between Series
Convert From	Type N Plug	Type N Plug
Convert To	3.5mm Plug	3.5mm Jack
Impedance	50-Ohm	50-Ohm
Price (Qty 1-9)	<b>\$ 129.95</b>	<b>\$ 109.95</b>

- To order on-line visit: <https://4gte.com/catalogsearch/result/?q=PA5125>
- To order by phone call us at 866-409-0400
- To order via with Net 30 terms, e-mail us at [sales@4gte.com](mailto:sales@4gte.com)





 www.VelocitybyGTE.com		<b>SUSTAINABLE SOLUTIONS</b> <ul style="list-style-type: none"> <li>• Save Money</li> <li>• Save Time</li> <li>• Save the Environment</li> </ul>
<b>Repairable Test Cables</b> 	<b>Connector Gage Sets</b> 	<b>Connector Torque Wrenches</b> 



## Type N to SMA Adapters in Stock




				
	<b>PA5121A</b>	<b>PA5121B</b>	<b>PA5121C</b>	<b>PA5121D</b>
Application	Precision Adapter	Precision Adapter	Precision Adapter	Precision Adapter
Compliance RoHS	Yes	Yes	Yes	Yes
Frequency Range	DC-18 GHz	DC-18 GHz	DC-18 GHz	DC-18 GHz
VSWR	1.15 Max DC-11 GHz 1.20 Max 11-18 GHz	1.15 Max DC-11 GHz 1.20 Max 11-18 GHz	1.15 Max DC-11 GHz 1.20 Max 11-18 GHz	1.15 Max DC-11 GHz 1.20 Max 11-18 GHz
Temperature	-55°C~+165°C	-55°C~+165°C	-55°C~+165°C	-55°C~+165°C
Body Material	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel
Body Finish	Passivated	Passivated	Passivated	Passivated
Contact Material	Beryllium Copper Alloy	Beryllium Copper Alloy	Beryllium Copper Alloy	Beryllium Copper Alloy
Contact Finish	Gold	Gold	Gold	Gold
Insulator	PTFE	PTFE	PTFE	PTFE
Product Type	Between Series	Between Series	Between Series	Between Series
Convert From	Type N Plug	Type N Plug	Type N Jack	Type N Jack
Convert To	SMA Plug	SMA Jack	SMA Jack	SMA Plug
Impedance	50-Ohm	50-Ohm	50-Ohm	50-Ohm
Price (Qty 1-9)	<b>\$ 79.95</b>	<b>\$ 42.95</b>	<b>\$ 59.95</b>	<b>\$ 59.95</b>

- To order on-line visit: <https://4gte.com/catalogsearch/result/?q=PA5121>
- To order by phone call us at 866-409-0400
- To order via with Net 30 terms, e-mail us at [sales@4gte.com](mailto:sales@4gte.com)




 <p><b>VELOCITY</b> MICROWAVE www.VelocitybyGTE.com</p>		<p><b>SUSTAINABLE SOLUTIONS</b></p> <ul style="list-style-type: none"> <li>• Save Money</li> <li>• Save Time</li> <li>• Save the Environment</li> </ul>
<p><b>Repairable Test Cables</b></p> 	<p><b>Connector Gage Sets</b></p> 	<p><b>Connector Torque Wrenches</b></p> 



## BNC to SMA Adapters in Stock

			
	<b>PA2131A</b>	<b>PA2131B</b>	<b>PA2131D</b>
Application	Precision Adapter	Precision Adapter	Precision Adapter
Compliance RoHS	Yes	Yes	Yes
Frequency Range	DC-8 GHz	DC-8 GHz	DC-8 GHz
VSWR	1.15 Max	1.15 Max	1.15 Max
Temperature	-55°C~+125°C	-55°C~+125°C	-55°C~+125°C
Body Material	Stainless Steel	Stainless Steel	Stainless Steel
Body Finish	Passivated	Passivated	Passivated
Contact Material	Beryllium Copper Alloy	Beryllium Copper Alloy	Beryllium Copper Alloy
Contact Finish	Gold	Gold	Gold
Insulator	PTFE & PEI	PTFE & PEI	PTFE & PEI
Product Type	Between Series	Between Series	Between Series
Convert From	BNC Plug	BNC Plug	BNC Jack
Convert To	SMA Plug	SMA Jack	SMA Plug
Impedance	50-Ohm	50-Ohm	50-Ohm
Price (Qty 1-9)	<b>\$ 29.00</b>	<b>\$ 29.00</b>	<b>\$ 29.00</b>

- To order on-line visit: <https://4gte.com/catalogsearch/result/?q=PA2131>
- To order by phone call us at 866-409-0400
- To order via with Net 30 terms, e-mail us at [sales@4gte.com](mailto:sales@4gte.com)

 <p><b>VELOCITY</b> MICROWAVE www.VelocitybyGTE.com</p>		<p><b>SUSTAINABLE SOLUTIONS</b></p> <ul style="list-style-type: none"> <li>• Save Money</li> <li>• Save Time</li> <li>• Save the Environment</li> </ul>
<p><b>Repairable Test Cables</b></p> 	<p><b>Connector Gage Sets</b></p> 	<p><b>Connector Torque Wrenches</b></p> 